

LSW single needle series (plain)

High speed, Compound feed and walking foot,
Large vertical axis hook, Reverse stitch, Lockstitch machines



Variety



LSW-8BL

Compound feed and walking foot, reverse stitch




LSW-8BL/CS

Compound feed and walking foot, reverse stitch, coarse(long) stitch

Applications

For sewing medium to heavy weight fabrics, leather, vinyl, synthetics and laminated and coated materials

Suitable for sewing such as boat and furniture upholstery, tarpaulins, covers, awnings, tents, umbrellas, handbags, luggage, travelware accessories, sports and camping equipment, wearing apparel, outdoor clothing, footwear and orthopedic appliances.



LSW single needle series (plain)

Features

- Semi-Automatic lubrication system.
- Large vertical axis hook (2.0 times).
- Automatic hook lubrication.
- Safety clutch prevents the hook from being damaged.
- Reverse stitching.
- Available in "THICK THREAD VERSION"(for heavier material). Add suffix "TA" when ordering.
- Synchronized cloth puller available (add suffix "R").
- 18 inch long arm version available (LLW series).
- Special cloth guide (AT-5676) available.

Specifications (LSW-)

Variety	8BL	8BL/CS
Number of needle	Single needle	
Max. sewing speed	2800(s.p.m.)	
Max. stitch length	1/4" (6.5 mm)	25/64" (10 mm)
Clearance under presser foot	by knee	5/8" (16 mm)
	by hand	21/64" (8.5 mm)
Needle bar stroke	1-5/16" (33.2 mm)	
Needle(standard)	DPx17 (#22) , 135x17 (#140)	
Thread	#8 (standard)	
Hook	Large vertical axis hook (2.0 times)	
Amount of lift of alternating presser foot	1/8"-15/64" standard 5/32" (3 - 6 mm) (standard 4 mm)	
Thread take up lever	Slide type	
Lubrication	Semi-automatic type	
Bed size	18-25/32"x 7" (477 x 177 mm)	
Working space	10-5/32"x 4-21/64" (258 x 110 mm)	
Motor	Clutch motor	
Net weight(Head only)	30Kg	32Kg

NOTE

- (1) Speed depends on threads, materials and type of operation
- (2) Specifications subject to change without notice

Available model version

- * LSW-8BLV Single needle, compound feed and alternating pressers, synchronized binder
- * LSW-8BLM Single needle, compound feed and alternating pressers, edge trimming (right)
- * LSW-8BLVMF Single needle, compound feed and alternating pressers, edge trimming (center)
- * LSW-8LVMF Single needle, compound feed and alternating pressers, edge trimming (center), without reverse stitch



SEIKO SEWING MACHINE CO., LTD.

1-11-3, Imado, Taito-ku, Tokyo 111-8534, Japan
 Phone : +81-3-3872-6173 (Overseas dept.)
 Fax : +81-3-3873-6596
 E-mail : export@seiko-sewing.co.jp

Printed in Japan 2003.08

<http://www.seiko-sewing.co.jp/>